

ALCOHOL CARE FC2.0

L'etilometro offre misurazioni precise del BAC ($\pm 0,050\%$), grazie alla tecnologia avanzata **FUEL CELL**. Portatile e intuitivo, è ideale per test rapidi in ambito professionale e privato.



- ➔ **Alta precisione:** tecnologia professionale Fuel Cell
- ➔ **APP inclusa:** interfaccia semplice, memoria illimitata
- ➔ **Intelligente:** Sensore di mancato rilevamento
- ➔ **Allarme integrato** per superamento limiti
- ➔ **Certificazioni:** Conformità CE, ROHS e FCC
- ➔ **Portatile:** Peso leggero, dimensioni compatte
- ➔ **Sicurezza:** NO rischio sostanze interferenti
- ➔ **Varie unità di misura** (mg/L, g/L, %BAC)



Massima precisione per chi non accetta compromessi.



Download the app



AlcoCHECK

RISULTATO IN 5 SEC



TECNOLOGIA USATA DALLA POLIZIA



Model	AT808	Testing Time	< 5 Sec
Sensor Type	Platinum fuel cell	Display	LCD
Detection Range	0.00 - 0.40%BAC; 0.00-4.00‰BAC 0.00 - 2.00mg/L; 0.00 - 4.00g/L	Power	2*AAA battery
Accuracy	$\pm 0.005@ 0.05\%$ BAC	Working Environment	0°C - 50°C, $\leq 95\%$ RH, No dews
Alarm point	0.05%BAC; 0.50‰BAC; 0.25mg/L; 0.50g/L; (adjustable) < 5 Sec	Dimensions	105*45*16mm@58g
		Records	99 (device); unlimited (app)
		App Name	AlcoCHECK

ALCOHOL CARE SC1.0

Un tester per alcol economico, preciso e portatile, dotato di sensore a superficie piatta, ideale per l'uso personale. Fornisce risultati affidabili in pochi secondi con un design compatto e intuitivo.



- ➔ **Otti m a p r e c i s i o n e**: tecnologia Semiconduttore
- ➔ Risposta rapida e risultati affidabili
- ➔ **Allarme integrato** per superamento limiti
- ➔ **Certificazioni**: Conformità CE, ROHS e FCC
- ➔ **Portatile** : Peso leggero, dimensioni compatte
- ➔ Varie unità di misura (mg/L, g/L, %BAC)

Affidabilità accessibile: il test dell'alcol a portata di tutti!

RISULTATO IN 8 SEC



Sensor Type	Semiconductor Sensor	Testing Time	< 8 s
Detection Range	0.00 - 0.20%BAC, 0.00-2.00%BAC 0.00 - 1.00mg/L; 0.00 - 2.00g/L	Display	1.0-inch LCD
		Power	2×AA batteries
Accuracy	± 0.01%BAC at 0.05%BAC	Working Environment	0°C - 50°C, ≤95% RH, No dews
Pre-set Level	0.05%BAC; 0.50%BAC; 0.25mg/L; 0.50g/L	Working Time	> 00 blowing times (full charge)
		Dimensions	123mm*44mm*19mm @50g
Warm-up Time	about 35s	Unit	switchable %BAC, %BAC, mg/L, g/L